

PORTABLE FIRE EXTINGUISHERS

10 LB. ABC Heavy Duty High Flow Stored Pressure Fire Extinguisher



DESCRIPTION

Buckeye's 10 lb. ABC Heavy Duty High Flow Fire Extinguisher is specifically designed to meet the demands of industrial applications where hazards of pressurized flammable liquids, pressurized gases, or the potential for three dimensional (flowing) fires exist. In these instances, NFPA 10 requires a fire extinguisher that contains a dry chemical agent and can discharge the agent at a rate of 1 lb./sec or greater. The Buckeye Heavy Duty High Flow extinguisher meets those requirements.

Typical uses; Tank Farms, Oil Rigs and Refineries, Fuel Depots, Industrial Gas Manufacturing, Marine Fueling Docks, and Gas Stations.

FEATURES

- Manufactured in accordance with ANSI/UL 299 and ANSI/UL 711 Standards. UL and ULC Listed as a High Flow Extinguisher.
- Equipped with a plated brass gage guard and a vinyl foot ring for additional protection against damage.
- Galvanizing compound coating with a baked on polyester epoxy powder coated steel cylinder. Plated brass valve assembly and stainless steel operating lever and handle. Passes a 3000-hour salt spray test.
- DOT and TC Compliant. US Coast Guard Approved with Model 812 Vehicle Bracket
- Trilingual labels; English, Spanish, and French
- ABC dry chemical is available in 50 lb. pails for recharging Buckeye extinguishers.

SPECIFICATIONS

Agent Capacity: 10 lbs. / 4.54 kg

UL/ULC Rating: 1A:20B:C

Shipping Weight: 19.0 lbs. / 8.6 kg

Height: 16.75 in / 42.5 cm

Width: 8.25 in / 21 cm

Cylinder Diameter: 6 in / 15.2 cm

Discharge Time: 10 seconds

Discharge Range: 30-40 ft. / 9.14-12.2 m

Operating Temperature Range: -65°F to 120°F / -54°C to 49°C

Operating Pressure: 195 psi

ORDERING INFORMATION

10 LB ABC Heavy Duty High Flow Dry Chemical Fire Extinguisher with Wall Hook-

Part # 11351

Note: For Coast Guard Approval, you must also order the Model 812 Vehicle Bracket, P/N 700230

Refer to the Buckeye Spare Parts List for replacement parts