



## PORTABLE FIRE EXTINGUISHERS

### 10 LB. Purple K High Flow Stored Pressure Fire Extinguisher



#### DESCRIPTION

Buckeye's 10 lb. Purple K (PK) High Flow Fire Extinguisher is specifically suited to meet the demands of industrial applications where hazards of pressurized flammable liquids, pressurized gases, or the potential for three dimensional (flowing) fires exists. In these instances, NFPA 10 requires a fire extinguisher that contains a dry chemical agent and can discharge the agent at a rate of 1 lb./sec. or greater. The Buckeye PK High Flow meets those requirements.

Typical uses; Tank Farms, Oil Rigs and Refineries, Fuel Depots, Industrial Gas Manufacturing, Marine Fueling Docks, and Gas Stations.

#### FEATURES

- Manufactured in accordance with ANSI/UL 299 and ANSI/UL 711 Standards. **UL and ULC Listed as a High Flow Extinguisher.**
- US COAST GUARD approved for Type B:C Size II when used in conjunction with Mounting Bracket Model 812, P/N 700230.
- DOT and TC Compliant
- Polyester epoxy powder coated steel cylinder with plated brass valve assembly and stainless steel operating lever and handle.
- Trilingual labels; English, Spanish, and French
- Purple K dry chemical is available in 50 lb. Pails for recharging Buckeye extinguishers.

#### SPECIFICATIONS

**Agent Capacity:** 10 lbs. / 4.54 kg

**UL/ULC Rating:** 20-B:C

**Shipping Weight:** 19.0 lbs. / 8.6 kg

**Height:** 16.75 in / 42.5 cm

**Width:** 8.25 in / 21 cm

**Cylinder Diameter:** 6 in / 15.2 cm

**Discharge Time:** 10 seconds

**Discharge Range:** 30-40 ft. / 9.14-12.2 m

**Operating Temperature Range:**  
-65°F to 120°F / -54°C to 49°C

**Operating Pressure:** 195 psi

#### ORDERING INFORMATION

**10 LB Purple K High Flow Dry Chemical Fire Extinguisher with Wall Hook-**

**Part No. 11650**

*Note: For Coast Guard Approval, you must also order the Model 812 Mounting Bracket, P/N 700230*

*Refer to the Buckeye Spare Parts List for replacement parts*