

PORTABLE WHEELED FIRE EXTINGUISHERS

K-150-RG PURPLE K DRY CHEMICAL PRESSURE REGULATED WHEELED FIRE EXTINGUISHER

DESCRIPTION

The K-150-RG Purple K (PK) Dry Chemical Pressure Regulated Wheeled Fire Extinguisher is a potassium bicarbonate-based fire extinguisher that is suitable for use on Class B and Class C fires.

Designed for one-man operation, these units are easily transportable through doorways and over rough terrain. Tow loops can be added if you need easy vehicle transport capability.

The K-150-RG is rechargeable.

Ideal for use at aircraft facilities, offshore rigs, ship docks, petroleum operations and refineries, chemical plants, construction sites, and storage and loading facilities.

FEATURES

- Manufactured in accordance with ANSI/UL 299 and ANSI/UL 711 Standards.
- · Key Features:
- Rugged steel cylinder in welded steel cart frame.
- Optional wheel sizes and configurations (See Ordering Information)
- All-metal valve and discharge nozzle.
- Baked on polyester epoxy powder coating on all steel surfaces for added corrosion resistance.
- Purple K Dry Chemical agent is available in 50 lb. containers for recharging Buckeye extinguishers. (Part Number 61200)

SPECIFICATIONS

Agent Capacity: 125 lbs. (56.7 kg)

UL Rating: 320-B:C

Approx. Weight: 387 lbs. (176 kg)- P/N 31320

422 lbs. (191 kg)- P/N 31340 434 lbs. (197 kg)- P/N 31350

Height: 50 in. (127 cm)- P/N 31320

55 in. (139 cm)- P/N 31340 55 in. (139 cm)- P/N 31350

Width: 24 in. (61 cm)- P/N 31320

32 in. (81.3 cm)- P/N 31340 32 in. (81.3 cm)- P/N 31350

Discharge Time: 55 seconds

Discharge Hose Length: 50 ft. (15.2 m)

Discharge Range: 30 - 40 ft. (9.1-12.72 m)

Operating Pressure: 240 psi (1655 kPa)

Operating Temperature Range: -65° F to 120° F (-54° C to 49° C)

Nitrogen Cartridge Cylinder Size:

110 Cu. Ft.

ORDERING INFORMATION

Model K-150-RG
Purple K Dry Chemical
Wheeled Fire Extinguisher

P/N 31320- 16 in. Rubber Wheels

P/N 31340- 36 in. Steel Wheels

P/N 31350- 36 in. Steel Wheels w/ Rubber Tread

Refer to the Buckeye Spare Parts List for replacement parts