



PORTABLE WHEELED FIRE EXTINGUISHERS

K-150-RG PURPLE K DRY CHEMICAL PRESSURE REGULATED WHEELED FIRE EXTINGUISHER (ARAMCO SPL MODEL)

DESCRIPTION

The K-150-RG SPL Purple K Dry Chemical Pressure Regulated Wheeled Fire Extinguisher is a potassium bicarbonate-based fire extinguisher that is suitable for use on Class B and Class C fires.

Designed for one-man operation, these units are easily transportable through doorways and over rough terrain. Tow loops can be added if you need easy vehicle transport capability.

The K-150-RG SPL is rechargeable.

Ideal for use at aircraft facilities, offshore rigs, ship docks, petroleum operations and refineries, chemical plants, construction sites, and storage and loading facilities.

FEATURES

- Manufactured in accordance with ANSI/UL 299 and ANSI/UL 711 Standards.
- Key Features:
 - Rugged steel cylinder in welded steel cart frame.
 - 36" Diameter, 6" Wide steel wheels with mechanically fastened rubber tread.
 - All-metal valve and discharge nozzle.
 - Pressure Indicator incorporated into the Fill Cap.
 - Galvanizing compound coating with a baked on polyester epoxy powder coating on all steel surfaces for added corrosion resistance.
- Purple K Dry Chemical agent is available in 50 lb. containers for recharging Buckeye extinguishers. (Part Number 61200)

SPECIFICATIONS

Agent Capacity: 125 lbs. (56.7 kg)

UL Rating: 320-B:C

Approx. Weight: 434 lbs. (197 kg)

Height: 57.5 in. (146 cm)

Width: 32 in. (81.3 cm)

Discharge Time: 55 seconds

Discharge Hose Length: 50 ft. (15.2 m)

Discharge Range: 30 - 40 ft. (9.1-12.72 m)

Operating Pressure: 240 psi (1655 kPa)

Operating Temperature Range:
-65° F to 120° F (-54° C to 49° C)

ORDERING INFORMATION

**Model K-150-RG SPL
Purple K Dry Chemical
Wheeled Fire Extinguisher**

P/N 31340HD SPL

Refer to the Buckeye Spare Parts List for replacement parts