



PORTABLE FIRE EXTINGUISHERS

10 LB. Standard Stored Pressure Fire Extinguisher



DESCRIPTION

Buckeye's 10 lb. Standard (aka Regular) Fire Extinguisher is a high performance fire extinguisher utilizing a sodium bicarbonate-based extinguishing agent, one of the most effective agents for Class B and Class C fires.

Typical uses: For flammable liquid hazards in public areas such as offices, classrooms, multi-family residences, and parking garages. For flammable liquid fires in commercial operations such as industrial facilities, sanitation facilities, vehicle service centers, and healthcare facilities.

FEATURES

- Manufactured in accordance with ANSI/UL 299 and ANSI/UL 711 Standards.
- US COAST GUARD approved for Type B:C Size II when used in conjunction with Mounting Bracket Model 809, P/N 700226.
- DOT and TC Compliant
- Polyester epoxy powder coated steel cylinder with all-metal valve assembly, operating lever, and handle.
- Color coded pressure gauge for easy verification of pressure status.
- Trilingual labels; English, Spanish, and French.
- Rechargeable for repeated usage.
- Standard dry chemical is available in 50 lb. Pails for recharging Buckeye extinguishers.

SPECIFICATIONS

Agent Capacity: 10 lbs. / 4.54 kg

UL/ULC Rating: 40-B:C

Shipping Weight: 18.25 lbs. / 8.3 kg

Height: 21 in / 53.3 cm

Width: 7.75 in / 19.7 cm

Cylinder Diameter: 5.125 in / 13 cm

Discharge Time: 14 seconds

Discharge Range: 15-21 ft. / 4.6-6.4 m

Operating Temperature Range:

-65°F to 120°F / -54°C to 49°C

Operating Pressure: 195 psi

ORDERING INFORMATION

10 LB Standard Dry Chemical Fire Extinguisher with Wall Hook- Part No. 11840

Note: For Coast Guard Approval, you must also order the Model 809 Mounting Bracket, P/N 700226

Refer to the Buckeye Spare Parts List for replacement parts