



## PORTABLE FIRE EXTINGUISHERS

### 20 LB. CARBON DIOXIDE STORED PRESSURE FIRE EXTINGUISHER

#### DESCRIPTION

Buckeye's 20 LB Carbon Dioxide Fire extinguisher is used on "B" and "C" class fires.

It is ideal for use in chemical and manufacturing plants, oil rigs, rail yards, warehouses, construction sites, parking garages, boat docks, and large laboratories.

#### FEATURES

- Manufactured in accordance with ANSI/UL 154 and ANSI/UL 711 Standards. USDOT compliant cylinders are tested to 3000 psi.
- US COAST GUARD approved for Type B:C Size II when used in conjunction with Mounting Bracket Model 811, P/N 700229.
- Polyester epoxy powder coated aluminum cylinder, rugged plated brass valve, and stainless steel handle and lever.
- Carbon Dioxide is a residue-free extinguishing agent that is environmentally friendly. Carbon Dioxide has an Ozone Depletion Potential (ODP) of 0 and a Global Warming Potential (GWP) of 1.

#### SPECIFICATIONS

**Agent Capacity:** 20 lbs / 9.07 kg

**UL Rating:** 10-B:C

**Shipping Weight:** 49.0 lbs / 22.2 kg

**Height:** 26.875 in / 68.2 cm

**Width:** 13.0 in / 33.0 cm

**Cylinder Diameter:** 8.0 in / 20.3 cm

**Discharge Time:** 20 seconds

**Discharge Range:** 4 – 8 ft / 1.2 – 2.4 m

**Operating Temperature Range:**  
-22° F to 120° F / -30° C to 49° C

#### ORDERING INFORMATION

**20 LB Carbon Dioxide Fire Extinguisher with Wall Hook**

P/N 46600

*Note: For Coast Guard Approval you must also order the Model 811 Mounting Bracket, P/N 700229*

*Refer to the Buckeye Spare Parts List for replacement parts*