



## 50 lb. and 100 lb. Carbon Dioxide Wheeled Stored Pressure Fire Extinguishers

The Buckeye 50 lb. and 100 lb. Carbon Dioxide Wheeled Stored Pressure Fire Extinguishers are portable fire extinguishers that are suitable for use on Class B and C fires. Residue-free for easy clean-up and nonconductive for operator safety, the Wheeled Carbon Dioxide extinguishers are an excellent choice where a large capacity, residue-free extinguisher is needed.

These extinguishers are built to withstand the often harsh environments of the locations where they are needed. Carbon steel cylinders and frames painted with a polyester epoxy topcoat ensure that these extinguishers are second to none in corrosion protection and durability.

Wheeled Carbon Dioxide extinguishers are ideal for protecting sensitive electronic equipment, refineries, shipboard use, manufacturing facilities, research facilities, chemical plants, and vehicle/aircraft/marine service centers.

### FEATURES

- Manufactured in accordance with ANSI/UL 154 and ANSI/UL 711 Standards
- Made in the USA
- Key Features:
  - USDOT compliant steel agent cylinders
  - Rugged welded steel cart frame
  - "no flat" solid rubber tires
  - Plated brass valves and impact resistant discharge horns
  - Carbon Dioxide is widely available for convenient recharge
  - Designed for one-man operation
  - Easily portable through doorways and hallways



35050

### Specifications

Model No.	C-50-SE	C-100-SE
Part No.	35050	35100
Agent Capacity	50 lbs. / 22.68 kg	100 lbs. / 45.36 kg
UL Rating	20B:C	20B:C
Discharge Time	40 seconds	80 Seconds
Discharge Range	15 ft. 4.6 m	15 ft. 4.6 m
Operating Temperature Range	-22° to 120°F -30° to 49°C	-22° to 120°F -30° to 49°C
Unit Weight	286 lbs. / 130 kg	416 lbs. / 189 kg
Unit Height	60 in. / 152 cm	65 in. / 165.1 cm
Unit Width	31 in. / 78.7 cm	30 in. / 76.2 cm
Unit Depth	21 in / 53.3 cm	21 in / 53.3 cm
Discharge Hose Diameter and Length	.50 in. x 15 ft. 1.27 cm x 4.6 m	.50 in. x 40 ft. 1.27 cm x 4.6 m



35100