



65 lb. and 150 lb. Halotron I™ Wheeled Stored Pressure Fire Extinguishers

The Buckeye 65 lb. and 150 lb. Halotron I™ Wheeled Stored Pressure Fire Extinguishers are “clean agent” fire extinguishers that are suitable for use on Class A, B, and C fires. Residue-free for easy clean-up, nonconductive for operator safety, and earth-friendly with extremely low ozone depletion and global warming potential, Wheeled Halotron extinguishers make excellent replacements for Halon 1211 extinguishers.

The Buckeye Wheeled Halotron I extinguishers are designed to deliver exceptional performance in harsh environments.

Wheeled Halotron I™ extinguishers are ideal for protecting sensitive electronic equipment, research facilities, electronic data storage rooms, military electronics, aircraft ramps, and vehicle/aircraft/marine service centers.

FEATURES

- Manufactured in accordance with ANSI/UL 2129 and ANSI/UL 711 Standards
- Made in the USA
- Key Features:
 - DOT/TC compliant steel agent cylinders
 - Rugged welded steel cart frame (Tow loops are available upon request)
 - Galvanizing compound undercoating of all painted surfaces
 - Semi-pneumatic tires
 - Plated brass valves and discharge nozzles
 - Halotron I agent is available in 150 and 200 lb. stock cylinders for recharging

71500



Specifications

Model No.	W-65	W-150
Part No.	76501	71501
Agent Capacity	65 lbs. / 29.5 kg	150 lbs. / 68 kg
UL Rating	4A:60B:C	10A:120B:C
Discharge Time	20 seconds	30 Seconds
Discharge Range	15 – 25 ft. 4.6 – 7.6 m	23 – 36 ft. 7 – 10.7 m
Operating Pressure	150 psi / 1035 kPa	150 psi / 1035 kPa
Operating Temperature Range	-40° to 120°F -40° to 49°C	-40° to 120°F -40° to 49°C
Unit Weight	252 lbs. / 114 kg	396 lbs. / 180 kg
Unit Height	50 in. / 127 cm	62 in. / 157.5 cm
Unit Width	24 in. / 61 cm	24 in. / 61 cm
Unit Depth	41.5 in / 105 cm	41.5 in / 105 cm
Discharge Hose Diameter and Length	.75 in. x 25 ft. 1.9 cm x 7.6 m	.75 in. x 50 ft. 1.9 cm x 15.2 m

76500



6 Year Manufacturer’s Warranty