



## PORTABLE WHEELED FIRE EXTINGUISHERS

### A-150-RG ABC DRY CHEMICAL PRESSURE REGULATED WHEELED FIRE EXTINGUISHER (36 in. Steel Wheel Model)

#### DESCRIPTION

The A-150-RG ABC Dry Chemical Pressure Regulated Wheeled Fire Extinguisher is a Monoammonium Phosphate based fire extinguisher that is suitable for use on Class A, B and C fires.

Designed for one-man operation, these units are easily transportable through doorways and over rough terrain. Tow loops can be added if you need easy vehicle transport capability.

The A-150-RG is rechargeable.

Ideal for use at aircraft facilities, offshore rigs, ship docks, petroleum operations and refineries, chemical plants, construction sites, and storage and loading facilities.

#### FEATURES

- Manufactured in accordance with ANSI/UL 299 and ANSI/UL 711 Standards.
- Key Features:
  - Rugged steel cylinder in welded steel cart frame.
  - 36" Diameter steel wheels.
  - All-metal valve and discharge nozzle.
  - Baked on polyester epoxy powder coating on all steel surfaces for added corrosion resistance.
- ABC Dry Chemical agent is available in 50 lb. containers for recharging Buckeye extinguishers. (Part Number 61000)

#### SPECIFICATIONS

**Agent Capacity:** 125 lbs. (56.7 kg)

**UL Rating:** 30-A:240-B:C

**Approx. Weight:** 422 lbs. (191 kg)

**Height:** 55 in. (139 cm)

**Width:** 32 in. (81.3 cm)

**Discharge Time:** 44 seconds

**Discharge Hose Length:** 50 ft. (15.2 m)

**Discharge Range:** 30 - 40 ft. (9.1-12.72 m)

**Operating Pressure:** 240 psi (1655 kPa)

**Operating Temperature Range:**  
-65° F to 120° F (-54° C to 49° C)

#### ORDERING INFORMATION

**Model A-150-RG  
ABC Dry Chemical  
Wheeled Fire Extinguisher**

**P/N 31140**

*Refer to the Buckeye Spare Parts List for replacement parts*