



PORTABLE WHEELED FIRE EXTINGUISHERS

A-150-RG ABC DRY CHEMICAL PRESSURE REGULATED WHEELED FIRE EXTINGUISHER (16 in. Rubber Tire Model)

DESCRIPTION

The A-150-RG ABC Dry Chemical Pressure Regulated Wheeled Fire Extinguisher is a Monoammonium Phosphate based fire extinguisher that is suitable for use on Class A, B and C fires.

Designed for one-man operation, these units are easily transportable through doorways and over rough terrain. Tow loops can be added if you need easy vehicle transport capability.

The A-150-RG is rechargeable.

Ideal for use at aircraft facilities, offshore rigs, ship docks, petroleum operations and refineries, chemical plants, construction sites, and storage and loading facilities.

FEATURES

- Manufactured in accordance with ANSI/UL 299 and ANSI/UL 711 Standards.
- Key Features:
 - Rugged steel cylinder in welded steel cart frame.
 - 16" Diameter semi-pneumatic rubber tire.
 - All-metal valve and discharge nozzle.
 - Baked on polyester epoxy powder coating on all steel surfaces for added corrosion resistance.
- ABC Dry Chemical agent is available in 50 lb. containers for recharging Buckeye extinguishers. (Part Number 61000)

SPECIFICATIONS

Agent Capacity: 125 lbs. (56.7 kg)

UL Rating: 30-A:240-B:C

Approx. Weight: 387 lbs. (176 kg)

Height: 50 in. (127 cm)

Width: 24 in. (61 cm)

Discharge Time: 44 seconds

Discharge Hose Length: 50 ft. (15.2 m)

Discharge Range: 30 - 40 ft. (9.1-12.72 m)

Operating Pressure: 240 psi (1655 kPa)

Operating Temperature Range:

-65° F to 120° F (-54° C to 49° C)

ORDERING INFORMATION

**Model A-150-RG
ABC Dry Chemical
Wheeled Fire Extinguisher**

P/N 31120

Refer to the Buckeye Spare Parts List for replacement parts