



PORTABLE WHEELED FIRE EXTINGUISHERS

A-350-PT ABC DRY CHEMICAL WHEELED PRESSURE TRANSFER FIRE EXTINGUISHER

DESCRIPTION

The A-350-PT ABC Dry Chemical Wheeled Pressure Transfer Fire Extinguisher is a monoammonium phosphate-based fire extinguisher that is suitable for use on Class A, Class B, and Class C fires.

Designed for one-man operation, these units are easily transportable through doorways and over rough terrain. Tow loops can be added if you need easy vehicle transport capability.

The A-350-PT is rechargeable and can also be configured as a stationary unit.

Ideal for use on offshore rigs, ship docks, refineries, chemical plants, construction sites, and storage and loading facilities.

FEATURES

- Manufactured in accordance with ANSI/UL 299 and ANSI/UL 711 Standards.
- Key Features:
 - DOT/TC compliant steel cylinder
 - Rugged welded steel cart frame
 - 36 x 6 in. steel wheels
 - Epoxy powder coating
 - All-metal valve and discharge nozzles
 - Available with optional tow loop for vehicle transportability.
- ABC Dry Chemical agent is available in 50 lb. containers for recharging Buckeye extinguishers. (Part Number 61000)

SPECIFICATIONS

Agent Capacity: 300 lbs. / 136 kg

UL Rating: 30-A:320-B:C

Weight: 657 lbs. / 298 kg

Height: 58 in. / 147 cm

Width: 36 in. / 91.4 cm

Discharge Time: 53 seconds

Discharge Range: 30 - 40 ft. / 9.1-12.2 m

Operating Pressure: 240 psi / 1655 kPa

Operating Temperature Range:
-65° F to 120° F / -54° C to 49° C

ORDERING INFORMATION

**Model A-350-PT
ABC Dry Chemical
Wheeled Fire Extinguisher**

P/N 32110

Refer to the Buckeye Spare Parts List for replacement parts