

# MINI-GUARD AUTOMATIC SPOT PROTECTION Halotron I Clean Agent



**FEATURES:**

- Can be used in both total flood and local (spot) applications.
- Charged with Halotron I, a clean agent that is residue free and environmentally friendly. The agent is approved under the U.S. EPA SNAP program.
- Heat activated; requires no electrical power. Sprinkler Head rated at 165° F.
- Typical Installation Locations: computer server and electronic data storage rooms, cell tower equipment rooms, telephone switch panel closets, remote signal stations, and document storage rooms.
- Two mount styles available, vertical and horizontal. Horizontal mount requires bracket. Vertical mount has integrated mounting plate.
- Disposable. Do not require 6-yr. or 12 yr. inspection & maintenance. Discarded after 12 yrs. or discharge.
- Units are not intended as a substitute for an engineered system. Designed to provide supplementary fire protection.
- The cylinders are designed and tested to meet USDOT requirements.
- Made in the USA

**VERTICAL MOUNT**

Part No.	87100	87200
Agent Capacity	18 lbs. (8.2 kg)	25 lbs. (11.3 kg)
Ship Weight	29 lbs. (13.2 kg)	42 lbs. (19 kg)
Operating Pressure	100 psi (689 kPa) @ 70°F	
Storage Temperature Range	-40° to 120° F (-40° to 49° C)	
Length	16.50 in (41.9 cm)	17.75 in (45.1 cm)
Diameter	6.13 in (15.57 cm)	6.97 in (17.70 cm)
Max Total Flood Volume	500 cu. ft.	700 cu. ft.
Max. Local Application Coverage Area	4 x 4 ft.	6 x 6 ft.
Max. Height Above Hazard – Local Application	4 ft.	
Max. Height Above Hazard – Flood Application	8 ft.	10 ft.

**HORIZONTAL MOUNT**

Part No.	87105	87205
Agent Capacity	18 lbs. (8.2 kg)	25 lbs. (11.3 kg)
Ship Weight	29 lbs. (13.2 kg)	42 lbs. (19 kg)
Operating Pressure	100 psi (689 kPa) @ 70°F	
Storage Temperature Range	-40° to 120° F (-40° to 49° C)	
Length	17.875 in (45.4 cm)	21.875 in (55.6 cm)
Diameter	7 in (17.8 cm)	7.5 in (19.1 cm)
Max. Total Flood Volume	500 cu. ft.	700 cu. ft.
Max. Local Application Coverage Area	4 x 4 ft.	6 x 6 ft.
Max. Height Above Hazard – Local Application	4 ft.	
Max. Height Above Hazard – Flood Application	8 ft.	10 ft.
Mounting Bracket (Sold Separately)	700228	700229