



## PORTABLE WHEELED FIRE EXTINGUISHERS

### K-350-RG PURPLE K DRY CHEMICAL PRESSURE REGULATED WHEELED FIRE EXTINGUISHER

#### DESCRIPTION

The K-350-RG Purple K (PK) Dry Chemical Pressure Regulated Wheeled Fire Extinguisher is a Potassium Bicarbonate-based fire extinguisher that is suitable for use on Class B and C fires.

Designed for one-man operation, these units are easily transportable through doorways and over rough terrain. Tow loops can be added if you need easy vehicle transport capability.

The K-350-RG is rechargeable.

Ideal for use at aircraft facilities, offshore rigs, ship docks, petroleum operations and refineries, chemical plants, construction sites, and storage and loading facilities.

#### FEATURES

- Manufactured in accordance with ANSI/UL 299 and ANSI/UL 711 Standards.
- Key Features:
  - Rugged steel cylinder in welded steel cart frame.
  - 36" Diameter steel wheels. Optional rubber tread
  - All-metal valve and discharge nozzle.
  - Baked on polyester epoxy powder coating on all steel surfaces for added corrosion resistance.
- PK Dry Chemical agent is available in 50 lb. containers for recharging Buckeye extinguishers. (Part Number 61200)

#### SPECIFICATIONS

**Agent Capacity:** 300 lbs. (136 kg)

**UL Rating:** 320-B:C

**Approx. Weight:** 780 lbs. (354 kg)- P/N 32320  
806 lbs. (366 kg)- P/N 32340

**Height:** 58 in. (147 cm)

**Width:** 36 in. (91.4 cm)

**Discharge Time:** 57 seconds

**Discharge Hose Length:** 50 ft. (15.2 m)

**Discharge Range:** 30 - 40 ft. (9.1-12.72 m)

**Operating Pressure:** 240 psi (1655 kPa)

**Operating Temperature Range:**  
-65° F to 120° F (-54° C to 49° C)

**Nitrogen Cartridge Cylinder Size:**  
220 Cu. Ft.

#### ORDERING INFORMATION

**Model K-350-RG  
Purple K Dry Chemical  
Wheeled Fire Extinguisher**

**P/N 32320- 36 in. Steel Wheel**

**P/N 32340- 36 in. Steel Wheel w/ Rubber Tread**

*Refer to the Buckeye Spare Parts List for replacement parts*