



## PORTABLE FIRE EXTINGUISHERS

### 2.5 GALLON STORED PRESSURE WATER FIRE EXTINGUISHER

The Buckeye Water Fire Extinguisher provides effective and economical protection for Class A common combustible hazards.

The Water extinguisher uses plain water as its extinguishing agent and can be pressurized with air (or an inert gas such as nitrogen). With a Schrader valve incorporated into the valve assembly, recharging the unit quick, simple, and cost effective.

The extinguisher is manufactured, tested, and Listed to ANSI/UL 626 and ANSI/UL 711 Standards.

**Typical Uses:** For common combustible fires (fires fueled by wood, paper, cloth, etc.) in offices, classrooms, churches, hotel/motel assembly halls and guest areas.



SPECIFICATIONS	
Model	500
Part Number	50000
UL Rating	2A
Capacity	2.5 gallons (9.6 liters)
Operating Pressure	100 psi (690 kPa)
Discharge time (Seconds)	50
Discharge Range	45 – 55 ft. (13.7 – 16.8 m)
Temperature Range	40°F to 120°F (4.4°C to 49°C)
USCG Approval	Type A Size II
Cylinder Construction	Stainless Steel
Shipping Weight*	8.3 lbs. (3.7 kg) *Ships empty
Extinguisher Height	24.5 in (62.2 cm)
Width w/ Hose Installed	9 in (22.9 cm)
Cylinder Diameter	7 in (17.8 cm)
Standard Mounting Hardware	Wall Hook