



PORTABLE FIRE EXTINGUISHERS

6 LITER and 2.5 GALLON STORED PRESSURE FOAM FIRE EXTINGUISHER

DESCRIPTION

Buckeye's Foam Fire extinguishers contain the environmentally friendly Buckeye Platinum Plus C6 3% AFFF foam solution, an advanced formulation containing no PFOS and a PFOA content of less than 10 ppb (as of July 2020 the REACH limit is 25 ppb).

Underwriters Laboratory rated for both Class A and Class B fires, the extinguishers are extremely effective in combating Class B fires fueled by hydrocarbon type fuels such as gasoline, kerosene, and diesel. They also have excellent wetting characteristics when used to fight Class A type fires.

FEATURES

- Manufactured in accordance with ANSI/UL 8 and ANSI/UL 711 Standards and DOT compliant.
UL and ULC Listed
- Trilingual label: English, Spanish, and French.
- Stainless Steel cylinder with an all-metal valve assembly.
- Valve has Schrader valve connection for easy pressurizing.
- Extinguishers ship uncharged and unpressurized. Foam charge is included and has easy-to-follow mixing instructions.

SPECIFICATIONS

Agent Capacity:

Model FFE-6L: 6 liters (1.6 gallons)
Model FFE-2.5: 2.5 Gallons (9.46 liters)

UL/ULC Rating:

Model FFE-6L: 2-A:10-B
Model FFE-2.5: 3-A:20-B

Shipping Weight: (approx.)

Extinguisher ships uncharged
Model FFE-6L: 9 lbs. (4.08 kg)
Model FFE-2.5: 11 lbs. (4.99 kg)

Height:

Model FFE-6L: 19.25 in. / 48.9 cm
Model FFE-2.5: 25 in. / 63 cm

Width: (including hose/nozzle)

Model FFE-6L: 9 in. / 22.9 cm
Model FFE-2.5: 9 in. / 22.9 cm

Cylinder Diameter:

Model FFE-6L: 7 in. / 17.8 cm
Model FFE-2.5: 7 in. / 17.8 cm

Discharge Time:

Model FFE-6L: 37 seconds
Model FFE-2.5: 70 seconds

Discharge Range: 10-15 ft. / 3.05-4.57 m

Operating Temperature Range:

35°F to 120°F / 1.7°C to 49°C

ORDERING INFORMATION

Model FFE-6L Foam Fire Extinguisher
Order Part Number 56000

Model FFE-2.5 Foam Fire Extinguisher
Order Part Number 52500