

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 05/23/2024

Reviewed on 05/23/2024

1 Identification

Product Identifier

Trade Name: Buckeye C6 AFFF 3% Low Temperature AFFF Product Number: BFC-3.6LT Relevant identified uses of the substance or mixture and uses advised against: Fire-fighting foam concentrate. Product Description: Low-Temp 6% AFFF

Details of the Supplier of the Safety Data Sheet:

Manufacturer/Supplier: Buckeye Fire Equipment Company 110 Kings Road Kings Mountain, NC 28086 P: 704-739-7415 www.buckeyefire.com bfec@buckeyef.com Emergency telephone number: CHEMTREC, 24 hours Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1-703-527-3887 (collect calls accepted)

2 Hazard(s) Identification

Classification of the substance or mixture:

Eye Irritation 2B H320 Causes eye irritation.

Label elements:

Hazard pictograms: Non-Regulated Material Signal word: Warning

Hazard statements:

H320 Causes eye irritation.

Precautionary statements:

P264+P265 Wash thoroughly after handling. Do not touch eyes.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P317 If eye irritation persists: Get medical help.

Unknown acute toxicity:

This value refers to knowledge of known, established toxicological or ecotoxicological values. 0 % of the mixture consists of component(s) of unknown toxicity.

Classification system: NFPA/HMIS Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme NFPA ratings (scale 0 - 4)

100 Hea Fire Rea	
------------------------	--

HMIS-ratings (scale 0 - 4)

HEALTH1Health = 1FIRE0Fire = 0REACTIVITY0Physical Hazard = 0

Hazard(s) not otherwise classified (HNOC): None known



OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 05/23/2024

Reviewed on 05/23/2024

Trade Name: Buckeye C6 AFFF 3% Low Temperature AFFF

9	Comp	ocition/Int	Formation	on Ingredients
J	Compo	<i>Σ</i> ΓΙΙΟΠ/ΠΠ	ormation	on ingreaterits

Non-hazardous components:

7732-18-5 Water, distilled water, deionized water

25-50%

Chemical characterization: Substance

Description: Mixture of substances listed below with non-hazardous additions.

Dangerous Components:		
CAS: 57-55-6 RTECS: TY 2000000	Propylene Glycol	15-35%
CAS: 107-41-5 RTECS: SA 0810000	Hexylene Glycol Skin Irritation 2, H315; Eye Irritation 2A, H319; Flammable Liquids 4, H227	<15.000%
	Proprietary mixture of fluorosurfactants, hydro- < 5 N/A carbon surfactants, polysaccharides, and inorganic salts. ♦ Skin Irritation 2, H315; Eye Irritation 2B, H320	2-12%

Additional information:

The exact percentages of the ingredients of this mixture are considered to be proprietary and are withheld in accordance with the provisions of paragraph (i) of §1910.1200 of 29 CFR 1910.1200 Trade Secrets.

Buckeye Platinum Plus C6 3-6% ARAFFF does not contain PFOS and will not breakdown to yield PFOS in accordance with the goals of the US EPA 2010/15 PFOA Stewardship Program.

4 First-Aid Measures

Description of first aid measures

General information: If symptoms persist, call a physician.

After inhalation: In case of unconsciousness place patient stably in the side position for transportation. *After skin contact:*

Immediately wash with water and soap and rinse thoroughly.

If skin irritation occurs, consult a doctor.

Wash with plenty of soap and water. If irritation develops or persists, seek medical attention.

After eye contact:

Rinse opened eye for at least 15 minutes under running water. If symptoms persist, consult a doctor.

If easy to do so, remove contact lenses if worn.

If eye irritation occurs, consult a doctor.

Rinse opened eye for several minutes under running water.

Flush eyes at eye wash station for 15 minutes and repeat until pain-free. If irritation develops or persists or vision changes occur, seek medical attention.

After swallowing:

If swallowed and symptoms occur, consult a doctor.

If victim is conscious and alert, give 2-3 glasses of water to drink. Do not leave victim unattended. Seek immediate medical attention. On the advice of medical personnel, induce vomiting.

If vomiting occurs and the victim is conscious, give additional water to further dilute the chemical. Prevent aspiration of swallowed product by laying victim on side with head lower than their waist.

Information for doctor

Most important symptoms and effects, both acute and delayed:

Skin contact may aggravate existing chronic skin conditions.

Indication of any immediate medical attention and special treatment needed:

Treat symptomatically.

(Contd. on page 3)



OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 05/23/2024

Reviewed on 05/23/2024

Trade Name: Buckeye C6 AFFF 3% Low Temperature AFFF

Fire-Fighting Measures

Extinguishing media

Suitable extinguishing agents:

Use fire fighting measures that suit the environment.

This product is an extinguishing agent. It is nonflammable and noncombustible.

For safety reasons unsuitable extinguishing agents: No further relevant information.

Special hazards arising from the substance or mixture:

This product may decompose in fire and release oxides of sulfur and nitrogen (Refer to Section X) Advice for firefighters

Special protective equipment for firefighters:

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

6 Accidental Release Measures

Personal precautions, protective equipment and emergency procedures: Not required. Environmental precautions: Dilute with plenty of water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (i.e. sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation. Dispose of the collected material according to regulations.

Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

PAC-1:

57-55-6 Propylene Glycol	30 mg/m ³
107-41-5 Hexylene Glycol	2.3 ppm
PAC-2:	
EZ EE 6 Drapylana Chyaal	$1200mm^{3}$

57-55-6 Propylene Glycol	1,300 mg/m ³
107-41-5 Hexylene Glycol	25 ppm

PAC-3:

57-55-6 Propylene Glycol	7,900 mg/m³
107-41-5 Hexylene Glycol	150 ppm
llevelling and Clarage	

andling and Storage

Handling

Precautions for safe handling:

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Avoid eye, respiratory, and skin exposure. Use the appropriate personal protective equipment when handling. Wash thoroughly after handling (Refer to Section VIII).

Information about protection against explosions and fires: No special measures required.

(Contd. on page 4)



OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 05/23/2024

Reviewed on 05/23/2024

Trade Name: Buckeye C6 AFFF 3% Low Temperature AFFF

Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and receptacles:

Product should be stored in its original container or extinguisher. Use in well-ventilated areas. Do not mix with other extinguishing agents.

Information about storage in one common storage facility: Not required.

Further information about storage conditions: Keep receptacle tightly sealed.

Specific end use(s): No further relevant information available.

8 Exposure Controls/Personal Protection

Additional information about design of technical systems: No further data; see section 7.

Control parameters:

Components with occupational exposure limits:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituents have no known exposure limits.

57-55-6 Propylene Glycol

WEEL Long-term value: 10 mg/m³

107-41-5 Hexylene Glycol

REL Ceiling limit value: 125 mg/m³, 25 ppm

TLV Short-term value: 10** mg/m³, 50* ppm

Long-term value: 25* ppm

*vapor **inh. fraction, aerosol only

Additional information:

The lists that were valid during the creation of this SDS were used as basis.

Exposure controls:

Personal protective equipment

General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing and wash before reuse.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Breathing equipment:

During the use of this product on fires, exhaust gases and products of incomplete combustion are the main respiratory hazards. In the manufacture of this product, employers and employees must use their collective judgment in determining the on-the-job settings where the use of a respirator is prudent. The need for respiratory protection is not likely for short-term use in well-ventilated areas. Use air-purifying respirators or powered air-purifying respirators with organic vapor and amine cartridges for acute short-term exposures. Long term exposures may require the use of positive pressure supplied air respirators or self-contained breathing apparatus.

Protection of hands:



Protective gloves

Material of gloves: Nitrile rubber, NBR *Penetration time of glove material:* Not applicable.



Safety Data Sheet (SDS) OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 05/23/2024

Reviewed on 05/23/2024

Trade Name: Buckeye C6 AFFF 3% Low Temperature AFFF

Eye protection:



Tightly sealed goggles Limitation and supervision of exposure into the environment: None

<u>9 Physical and Chemical Properties</u>

Information on basic physical and chemica General Information	I properties
Appearance: Form: Color: Odor: Odor threshold:	Liquid Light tan Mild Not determined.
pH-value:	Not determined.
Change in condition Melting point/Melting range: Boiling point/Boiling range:	Not determined. 97 °C (206.6 °F)
Flash point:	None
Flammability (solid, gaseous):	Not applicable.
Auto igniting:	Not applicable
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not self-igniting.
Danger of explosion:	Product does not present an explosion hazard.
Explosion limits: Lower: Upper:	Not determined. Not determined.
Vapor pressure:	Not determined.
Density @ 20 °C (68 °F): Relative density: Vapor density: Evaporation rate:	1.03 g/cm³ (8.5954 lbs/gal) Not determined. Not determined. Not determined.
Solubility in / Miscibility with: Water:	Fully miscible.
Partition coefficient (n-octanol/water)): Not determined.
Viscosity: Dynamic: Kinematic:	Not determined. Not determined.
Solvent content: VOC content:	0.00 %

Contd. on page 6)



OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 05/23/2024

Reviewed on 05/23/2024

Trade Name: Buckeye C6 AFFF 3% Low Temperature AFFF

Solids content:

0.0 %

Other information:

No further relevant information available.

0 Stability and Reactivity

Reactivity: No further relevant information available.

Chemical stability: Product is stable under normal conditions.

Thermal decomposition / conditions to be avoided:

Not known, but oxides of sulfur and nitrogen may be formed.

Possibility of hazardous reactions: No dangerous reactions known.

Conditions to avoid: No further relevant information available.

Incompatible materials:

Strong acids, bases, and oxidizers. Reactive metals. Any material reactive with water. *Hazardous decomposition products:* No dangerous decomposition products known.

1 Toxicological Information

Information on toxicological effects:

Acute toxicity:

LD/LC50 values that are relevant for classification:				
57-55-6 Propylene Glycol				
Oral	LD50	20,000 mg/kg (Rat)		
Dermal	LD50	20,800 mg/kg (rabbit)		
Inhalative	LC50/96 hours	52,930 mg/l (Pimephales)		
	Intravenous	6,630 mg/kg (mouse)		
		6,423 mg/kg (Rat)		
		6,500 mg/kg (rabbit)		
107-41-5 I	107-41-5 Hexylene Glycol			
Oral	LD50	3,700 mg/kg (Rat)		
Dermal	LD50	8,560 mg/kg (rabbit)		

Primary irritant effect:

On the skin: Irritant to skin and mucous membranes.

On the eye: Irritating effect.

Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

Carcinogenic categories:

IARC (International Agency for Research on Cancer):
None of the ingredients are listed.

NTP (National Toxicology Program):
None of the ingredients are listed.

OSHA-Ca (Occupational Safety & Health Administration):
None of the ingredients are listed.

(Contd. on page 7)



OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 05/23/2024

Reviewed on 05/23/2024

Trade Name: Buckeye C6 AFFF 3% Low Temperature AFFF

1	2	Fr	nlo	nica	l Infe	orma	tion
				yica		911110	

Toxicity:

Aquatic toxicity:

57-55-6 Propylene Glycol

EC50 >10,000 mg/l (Daphnia)

Persistence and degradability: No further relevant information available.

Behavior in environmental systems:

Bioaccumulative potential: No further relevant information available.

Mobility in soil: No further relevant information available.

Additional ecological information:

General notes: Not known to be hazardous to water.

Results of PBT and vPvB assessment:

PBT: Not applicable.

vPvB: Not applicable.

Other adverse effects: No further relevant information available.

3 Disposal Considerations

Waste treatment methods

Recommendation:

Observe all federal, state and local environmental regulations when disposing of this material.

Uncleaned packaging

Recommendation: Disposal must be made according to official regulations. **Recommended cleansing agent:** Water, if necessary with cleansing agents.

4 Transport Information

UN-Number:	
DOT, ADR/ADN, IMDG, IATA	Non-Regulated Material
UN proper shipping name:	
DOT, ADR/ADN, IMDG, IATA	Non-Regulated Material
Transport hazard class(es):	
DOT, ADR/ADN, ADN, IMDG, IATA	
Class:	Non-Regulated Material
Packing group:	
DOT, ADR/ADN, IMDG, IATA	Non-Regulated Material
Environmental hazards:	Not applicable.
Special precautions for user:	Not applicable.
Transport in bulk according to Annex II o	of
MARPOL73/78 and the IBC Code:	Not applicable.
UN "Model Regulation":	Non-Regulated Material
F. Desculaters information	

15 Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture: No further relevant information available.

(Contd. on page 8)



OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 05/23/2024

Reviewed on 05/23/2024

Trade Name: Buckeye C6 AFFF 3% Low Temperature AFFF

SARA (Superfund Amendments and Reauthorization):

Section 355 (extremely hazardous substances):

None of the ingredients are listed.

Section 313 (Specific toxic chemical listings):

None of the ingredients are listed.

TSCA (Toxic Substances Control Act):

7732-18-5 Water, distilled water, deionized water

57-55-6 Propylene Glycol

107-41-5 Hexylene Glycol

Hazardous Air Pollutants

None of the ingredients are listed.

California Proposition 65:

Chemicals known to cause cancer:

None of the ingredients are listed.

Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

New Jersey Right-to-Know List:

57-55-6 Propylene Glycol

107-41-5 Hexylene Glycol

New Jersey Special Hazardous Substance List:

None of the ingredients are listed.

Pennsylvania Right-to-Know List:

57-55-6 Propylene Glycol

107-41-5 Hexylene Glycol

Pennsylvania Special Hazardous Substance List:

None of the ingredients are listed.

Carcinogenic categories:

EPA (Environmental Protection Agency):

None of the ingredients are listed.

TLV (Threshold Limit Value established by ACGIH):

None of the ingredients are listed.

NIOSH-Ca (National Institute for Occupational Safety and Health):

None of the ingredients are listed.

GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS). *Hazard pictograms:* Non-Regulated Material *Signal word:* Warning ACTIVE

ACTIVE

ACTIVE



OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 05/23/2024

Reviewed on 05/23/2024

Trade Name: Buckeye C6 AFFF 3% Low Temperature AFFF

Hazard statements:H320 Causes eye irritation.Precautionary statements:P264+P265Wash thoroughly after handling. Do not touch eyes.P305+P351+P338If in eyes: Rinse cautiously with water for several minutes. Remove contact
lenses, if present and easy to do. Continue rinsing.P337+P317If eye irritation persists: Get medical help.

National regulations:

The product is not subject to be labelled according with the prevailing version of the regulations on hazardous substances.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

6 Other Information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

Contact:

Abbreviations and acronyms:

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety and Health OSHA: Occupational Safety & Health Administration TLV: Threshold Limit Value PEL: Permissible Exposure Limit **REL: Recommended Exposure Limit** Flammable Liquids 4: Flammable liquids - Category 4 Skin Irritation 2: Skin corrosion/irritation - Category 2 Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A Eye Irritation 2B: Serious eye damage/eye irritation - Category 2B * Data compared to the previous version altered.

SDS created by MSDS Authoring Services www.msdsauthoring.com +1-877-204-9106