

CERTIFICATE OF COMPLIANCE

Certificate Number EX15403
Report Reference EX15403-1992-10-01
Date 2021-May-17

Issued to: BUCKEYE FIRE EQUIPMENT CO
110 KINGS RD
PO BOX 428
KINGS MOUNTAIN NC, 28086-0428 US

This is to certify that representative samples of DRY-CHEMICAL EXTINGUISHING SYSTEM UNITS,
SPECIFIC HAZARD TYPE
See Addendum Page for Product Designation(s).

Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.


Standard(s) for Safety: ANSI/CAN, UL/ULC 1254 Standard for Pre-Engineered Dry and Wet Chemical Extinguishing System Units

Additional Information: See the UL Online Certifications Directory at <https://iq.ulprospector.com> for additional information

This Certificate of Compliance does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number EX15403
Report Reference EX15403-1992-10-01
Date 2021-May-17

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Models

“BFI” Series Pre-engineered Dry Chemical Extinguishing System Units, stored pressure type, having the nominal charging capacities as outlined below.

These units are pressurized with nitrogen to an operating pressure of 450 psig (31 bar) at 70°F (21°C). The system units covered are intended for use within a temperature operating range of 0° to 130°F (-17.8°C to + 54.4°C).


These Buckeye “Industrial System” units are for use in Local Applications, General Total Flooding, Open Front Paint Spray Booths and Vehicle Paint Spray Booths.

A description of these dry chemical extinguishing system units, the design and installation limitations are contained in the Listee's Installation Manual, P/N BFI-TM dated June 1, 2021.

These Systems are intended for indoor hazard protection only.

Model numbers

BFI-17-ABC
BFI-25-BC
BFI-25-ABC
BFI-35-ABC
BFI-50-BC
BFI-50-ABC
BFI-50HF-ABC
BFI-75-ABC
BFI-100-ABC



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

