



Portable Fire Extinguishers

15 LB. CARBON DIOXIDE STORED PRESSURE FIRE EXTINGUISHER

DESCRIPTION

Buckeye's 15 lb. Carbon Dioxide Fire extinguisher is used on "B" and "C" class fires.

It is ideal for use in chemical and manufacturing plants, oil rigs, rail yards, warehouses, construction sites, parking garages, boat docks, and large laboratories.

FEATURES

- Manufactured in accordance with ANSI/UL 154 and ANSI/UL 711 Standards. USDOT compliant cylinders are tested to 3000 psi.
- US COAST GUARD approved for Type B:C Size II when used in conjunction with Mounting Bracket Model 810, P/N 700228.
- Polyester epoxy powder coated aluminum cylinder, rugged plated brass valve, and stainless steel handle and lever.
- Carbon Dioxide is a residue-free extinguishing agent that is environmentally friendly. Carbon Dioxide has an Ozone Depletion Potential (ODP) of 0 and a Global Warming Potential (GWP) of 1.

SPECIFICATIONS

Agent Capacity	15 lbs / 6.8 kg
UL/ULC Rating	10-B:C
Shipping Weight	37.75 lbs / 17.1 kg
Height	26.375 in / 67 cm
Width	12.0 in / 30.5 cm
Cylinder Diameter	6.89 in / 17.5 cm
Discharge Time	15 seconds
Discharge Range	4 – 8ft / 1.2 – 2.4m
Operating Temperature Range	-22° F to 120° F -30° C to 49° C

ORDERING INFORMATION

15 lb. Carbon Dioxide Fire Extinguisher with Wall Hook
P/N 46100

Note: For Coast Guard Approval you must also order the Model 810 Mounting Bracket, P/N 700228

Refer to the Buckeye Spare Parts List for replacement parts



📍 110 Kings Road, Kings Mountain, NC 28086-0428

☎ 704-739-7415 🖨 704-739-7418 🌐 www.buckeyef.com