

Portable Fire Extinguishers

2.5 LB HALOTRON I STORED PRESSURE FIRE EXTINGUISHER Fixed Nozzle Model

DESCRIPTION

The 2.5 LB Halotron I Stored Pressure Fire Extinguisher is a "clean agent" fire extinguisher, meaning it is residue-free. It is also earth-friendly. Extremely low in both ozone depletion and global warming potential, this extinguisher is an excellent replacement for halon 1211 extinguishers.

Ideal for use on computers, telephone switch rooms, electronic data storage equipment, basically anywhere you have sensitive electronic equipment.

FEATURES

- Manufactured in accordance with ANSI/UL 2129 and ANSI/UL 711 Standards.
- Steel cylinder with polyester epoxy powder coating and rugged all-metal valve assembly.
- Halotron I available in 40, 150, and 200 LB cylinders for recharging Buckeye extinguishers.

SPECIFICATIONS

Agent Capacity	2.5 lbs. / 1.13 kg
UL/ULC Rating	2-B:C
Shipping Weight	5.5 lbs. / 2.49 kg
Height	13.375 in / 34 cm
Width	5.625 in / 14.3 cm
Cylinder Diameter	3.375 in / 8.6 cm
Discharge Time	9 seconds
Discharge Range	6-10 ft. / 1.8 - 3 m
Operating Temperature Range	-40° F to 120° F -40° C to 49° C
Operating Pressure:	100 psi / 689 kPa

ORDERING INFORMATION

2.5 LB Fixed Nozzle Halotron Fire Extinguisher-Vehicle Bracket

P/N 70251

Refer to the Buckeye Spare Parts List for replacement parts











