

Portable Fire Extinguishers

15 LB HALOTRON I STORED PRESSURE FIRE EXTINGUISHER

DESCRIPTION

The 15 LB Halotron I Stored Pressure Fire Extinguisher is a "clean agent" fire extinguisher, meaning it is residue-free. It is also earth-friendly. Extremely low in both ozone depletion and global warming potential, this extinguisher is an excellent replacement for halon 1211 extinguishers.

Ideal for use on computers, telephone switch rooms, electronic data storage equipment, basically anywhere you have sensitive electronic equipment.

FEATURES

- Manufactured in accordance with ANSI/UL 2129 and ANSI/UL 711 Standards
- US COAST GUARD approved for Type B:C Size II when equipped with Bracket Model 810 P/N 700228 (sold separately).
- Steel cylinder with polyester epoxy powder coating and a rugged all-metal valve assembly.
- Halotron I is available in 40, 150, and 200 LB cylinders for recharging Buckeye extinguishers.

SPECIFICATIONS

Agent Capacity	15.5 lbs / 7.03 kg
UL/ULC Rating	2-A:10-B:C
Shipping Weight	25.75lbs / 11.75kg
Height	17.5 in / 44.5 cm
Width	8.625 in / 21.9 cm
Cylinder Diameter	7 in / 17.8 cm
Discharge Time	13 seconds
Discharge Range	12-18ft / 3.7-5.5m
Operating Temperature Range	-40° F to 120° F -40° C to 49° C
Operating Pressure:	125 psi / 862 kPa

ORDERING INFORMATION

15 LB Halotron Fire Extinguisher

Aluminum Valve- P/N 71550 Brass Valve - P/N 71551

Note: For Coast Guard Approval you must also order the Model 810 Mounting Bracket, P/N 700228

Refer to the Buckeye Spare Parts List for replacement parts





