



Portable Fire Extinguishers

20 LB. STANDARD STORED PRESSURE FIRE EXTINGUISHER

DESCRIPTION

Buckeye's 20 lb. Standard (STD) Fire Extinguisher is a high-performance fire extinguisher utilizing a sodium bicarbonate-based extinguishing agent, one of the most effective agents for Class B and Class C fires.

Typical uses: For flammable liquid hazards in public areas such as offices, classrooms, multi-family residences, and parking garages. For flammable liquid fires in commercial operations such as industrial facilities, sanitation facilities, vehicle service centers, and healthcare facilities.

FEATURES

- Manufactured in accordance with ANSI/UL 299 and ANSI/UL 711 Standards. UL and ULC Listed.
- DOT and TC Compliant. US Coast Guard Approved with Vehicle Bracket Model 811.
- Polyester epoxy powder coated steel cylinder with all-metal valve assembly, operating lever, and handle.
- Color coded pressure gauge for easy verification of pressure status.
- Rechargeable for repeated usage.
- Trilingual labels; English, Spanish, and French
- Standard dry chemical is available in 50 lb. Pails for recharging Buckeye extinguishers.

SPECIFICATIONS

Agent Capacity	20 lbs. / 9.07 kg
UL/ULC Rating	120B:C
Shipping Weight	33.5 lbs. / 15.2 kg
Height	21.25 in / 53.8 cm
Width	8.75 in / 22.2 cm
Cylinder Diameter	7.5 in / 19.1 cm
Discharge Time	28 seconds
Discharge Range	15-21 ft. / 4.6-6.4m
Operating Temperature Range	-65° F to 120° F -54° C to 49° C
Operating Pressure	195 psi

ORDERING INFORMATION

20 LB Standard Dry Chemical Fire Extinguisher with Wall Hook

Part No: 12220

Note: For Coast Guard Approval, you must also order the Model 811 Vehicle Bracket, P/N 700229

Refer to the Buckeye Spare Parts List for replacement parts



📍 110 Kings Road, Kings Mountain, NC 28086-0428

☎ 704-739-7415 📠 704-739-7418 🌐 www.buckeyef.com